



ITERANT A/500-C

ANTI-STICKING AGENT FOR METAL SURFACES

GENERAL INFORMATION AND BENEFITS

- ITERANT A/500-C performs an anti-adherent function for rubber and metal compacting rollers, paver-finishers and truck bodies, avoiding asphalt concrete adhesion.
- It is easily dilutable in water.

DOSAGE

- Variable depending on the conditions of use.
- The dilution varies according to the intended use. Indicatively:

TRUCK BODIES	AC with NEAT BITUMEN	1 part with 3 - 5 parts of water
	AC with MODIFIED BITUMEN	1 part with 1 - 3 parts of water
COMPACTING ROLLERS	AC with NEAT BITUMEN	1 part with 20 parts of water
	AC with MODIFIED BITUMEN	1 part with 10 parts of water

* 1:5 emulsion stability guaranteed up to a maximum of 4 hours.

COMPOSITION

Mixture of oils of different nature.

PROPERTIES

Aspect	liquid
Colour	yellow - dark brown
Density at 25°C	0.85 - 0.95 g/cm ³
Viscosity at 25°C	15 - 25 cP
Flash point	≥ 150°C
Pour point	≤ 0°C

PACKAGING AND STORAGE

Drums or IBCs.

Store in the original packaging, away from heat sources and sheltered from adverse weather and UV rays.

REV 00-19

The above information is based on our current knowledge and experience. Under no circumstances are any warranties expressed or implied. We assume no liabilities as proper use of our products is beyond our control. For safety precautions, please see the product's MSDS.