

DATA SHEET

Auger Power Head



16-T0009_L and 16-T0009_M

General description

Used in conjunction with sampling tube to obtain disturbed or indisturbed samples of soils. Two models available.

Specifications

Models	16-T0009/L	16-T0009/M
Piston displacement (cc)	44,9	135
Engine (Hp)	2, two stroke	4,5 four stroke
Fuel	Fuel mixture	Gasoline
Ignition	Electronic	Electronic
Augers	80 mm dia.x 800 mm length included	Not included see accessories
Max. drilling capacity (dia.)	220 mm	400 mm
Max drilling depth	1.4 m	2 m
Operation	One operator	Two operators
Weight approx.: kg	10,5	27



DATA SHEET

Products

16-T0009/L

Auger power head, 1,62 kW, for holes up to 220 mm dia. Complete with 80x800 mm auger

16-T0009/M

Auger power head, 4,5 HP Honda 4-strokes engine, heavy duty reduction gear, complete with reversing gear, for holes up to 400 mm dia.

Accessories and consumables

16-T0009/MEX

Extension rod for augers, 1 mt long

16-T0009/M1

Auger dia. 100x1000 mm

16-T0009/M2

Auger dia. 150x1000 mm

16-T0009/M3

Auger dia. 200x1000 mm