

## DATA SHEET

### Kumagawa Extractor



75-B0018

#### General description

Used for the quantitative determination of bitumen in hot-mixed paving mixtures and pavement samples. It consists of a balloon, cooling unit, Dean-Stark stopcock, electric heating mantle with regulator and fittings.

Two models available: 1 liter and 2 liter capacity. The filtering cartridges are not part of the apparatus and have to be ordered separately. See accessories.

The solvent used can be profitably recovered with the solvent recovery unit.

- Weight approx.: 15 kg

#### Standards

- EN 12697-1

#### Products

##### 75-B0018

Kumagawa extractor apparatus, 1 litre capacity. 230V/50-60Hz/1ph

##### 75-B0018/Z

Kumagawa extractor apparatus, 1 litre capacity. 110V/60Hz/1ph

##### 75-B0018/A

Kumagawa extraction apparatus 2 litre capacity. 230V/50Hz/1Ph

##### 75-B0018/AZ

Kumagawa extraction apparatus 2 litre capacity. 110V/60Hz/1Ph

## DATA SHEET

---

### Accessories and consumables

#### **75-B0018/1**

Kumagawa cartridge dia 58 x 170 mm. Pack of 25

#### **75-B0018/A1**

Kumagawa cartridge dia 80 x 200 mm. for 2 litre cap. apparatus. Pack of 25

#### **75-B0018/A2**

Kumagawa cartridge dia 80 x 250 mm. Pack of 25