

## DATA SHEET

# Sand Patch Apparatus



80-B0179

## General description

This test is performed spreading a measured volume of glass spheres (ASTM and EN) or fine sand (NF) into a circular patch on the road surface and filling the surface depressions to the level of the peaks. The apparatus comprises the following parts:

- Measuring brass cylinder
- Spreader disc with surface covered by rubber
- Glass sand or glass spheres containers with screw top and pouring hole. Q.ty 2
- Screw-adjusted dividers
- 300 mm rule
- Brush
- Wind shield
- Kneeling pad
- Plastic measuring cylinder 10 ml cap
- Plastic measuring cylinder 25 ml cap
- Plastic measuring cylinder 50 ml cap

Weight approx.: 3 kg

## Standards

- EN 13036-1
- ASTM E965
- NF P98 216-1

## Products

**80-B0179**

Sand patch apparatus

## DATA SHEET

### Accessories and consumables

#### **80-B0179/2**

Natural sand 150/75 microns 10 kg

#### **80-B0179/3**

Natural sand 315/160 microns. Pack of 10 kg

#### **80-B0179/30**

Measuring cylinder

#### **80-B0179/31**

Sand spreader disc

#### **80-B0179/5**

Solid glass spheres 180/250 micron. Pack of 25 kg

#### **80-B0179/6**

Solid glass spheres 180/250 micron. Pack of 5 kg