

Product Code

UTS-0790	Adjustable Stem and Perforated Aluminum Plate for CBR Swelling Test
UTS-0790A	Adjustable Stem and Perforated Brass Plate, ASTM, for CBR Swelling Test
UTS-0790NF	Adjustable Stem and Perforated Plastic Plate,NF, for CBR Swelling Test
UTS-0790AS	Adjustable Stem and Perforated Plate, AS, for CBR Swelling Test
UTS-0792A	Tripod for CBR Swelling Test, ASTM, AS.For UTS-0700 and UTS-0740AS
UTS-0792E	Tripod for CBR Swelling Test, EN, for UTS-0612
UTS-0792	Tripod for CBR Swelling Test, BS, NF, TS
UTGM-0120	Analog Gauge 30 mm Travel x 0.01 mm Division
UTGM-0148	Digital Dial Gauge 25x0,01 mm, LCD Display
UTGM-0152	Digital Dial Gauge 12,7x0,001 mm, LCD Display
UTS-0794	CBR Soaking Tank (6 pcs. CBR Mould Capacity)

Standards

EN 13286-47; ASTM D1183; AASHTO T193; BS 1377:4, 1924:2; NF P 94-078; AS 1289.6.1.1

This equipment is used to monitor the swelling by placing it on top of the soil sample. The swell test consists of perforated plate (swell plate) with adjustable stem, dial gauge and dial gauge tripod for mounting swell dial gauge in position on CBR Mould Collar.

The preferred gauge and each other equipment should be ordered separately for swelling test.

Product Code	Dimensions	Weight
UTS-0790	180x180x160 mm	2.5 kg
UTS-0790NF	180x180x160 mm	0,5 kg
UTS-0792	200x200x300 mm	1 kg
UTGM-0120	150x100x80 mm	0.5 kg
UTS-0794	500x700x400 mm	3 kg

